

TURNBUCKLES

WORKING LOAD LIMIT	THREAD DIAM IN INC	WEIGHT IN kg	BODY DIMENSIONS						
			A	B	C	D	E	G	H
/kg									
227	1/4 x 4	0.068	4.75	4.00	0.38	0.72	0.34	0.50	0.38
363	5/16 x 4 1/2	0.086	5.44	4.50	0.47	0.81	0.38	0.56	0.44
544	3/8 x 6	0.132	7.12	6.00	0.56	0.88	0.38	0.62	0.50
998	1/2 x 6	0.272	7.50	6.00	0.75	1.12	0.50	0.81	0.62
998	1/2 x 9	0.308	10.50	9.00	0.75	1.12	0.50	0.81	0.62
998	1/2 x 12	0.453	13.50	12.00	0.75	1.12	0.50	0.81	0.62
1587	5/8 x 6	0.408	7.88	6.00	0.94	1.38	0.62	1.00	0.75
1587	5/8 x 9	0.535	10.88	9.00	0.94	1.38	0.62	1.00	0.75
1587	5/8 x 12	0.648	13.88	12.00	0.94	1.38	0.62	1.00	0.75
2358	3/4 x 6	0.590	8.25	6.00	1.12	1.69	0.75	1.12	0.94
2358	3/4 x 9	0.794	11.25	9.00	1.12	1.69	0.75	1.12	0.94
2358	3/4 x 12	0.943	14.25	12.00	1.12	1.69	0.75	1.12	0.94
2358	3/4 x 18	1.133	20.25	18.00	1.12	1.69	0.75	1.12	0.94
3265	7/8 x 12	1.224	14.62	12.00	1.31	1.94	0.88	1.31	1.06
3265	7/8 x 18	1.723	20.62	18.00	1.31	1.94	0.88	1.31	1.06
4535	1 x 6	1.124	9.00	6.00	1.50	2.25	1.00	1.50	1.25
4535	1 x 12	1.782	15.00	12.00	1.50	2.25	1.00	1.50	1.25
4535	1 x 18	2.394	21.00	18.00	1.50	2.25	1.00	1.50	1.25
4535	1 x 24	3.346	27.00	24.00	1.50	2.25	1.00	1.50	1.25
6893	1 1/4 x 12	2.380	15.12	12.00	1.56	2.62	1.25	1.88	1.50
6893	1 1/4 x 18	3.514	21.12	18.00	1.56	2.62	1.25	1.88	1.50
6893	1 1/4 x 24	4.612	27.12	24.00	1.56	2.62	1.25	1.88	1.50
9705	1 1/2 x 12	3.968	15.75	12.00	1.88	3.00	1.50	2.25	1.75
9705	1 1/2 x 18	4.988	21.75	18.00	1.88	3.00	1.50	2.25	1.75
9705	1 1/2 x 24	6.208	27.75	24.00	1.88	3.00	1.50	2.25	1.75

