

# WELDED LINK CHAIN DIN 763



SIZE		INSIDE LENGTH		INSIDE WIDTH	OUTSIDE WIDTH	TEST LOAD	BREAKING LOAD	WEIGHT PER M
MM	±MM	MM	±MM	MM	MM	KG	KG	KG
6	0,5	42	2	12	24	450	1427	0.63
7		49	2.5	14	28	610	1835	0.86
8		52	2.5	16	32	815	2548	1.10
9		59	3.0	18	36	1070	3262	1.41
10	1	65	3.2	20	40	1270	4077	1.75
11		72	3.4	22	44	1610	4842	2.11
12		78	3.6	24	48	1910	5759	2.55
13		82	4	26	52	2160	6422	2.95
16		100	5	32	64	3360	10194	4.45
18		113	5.2	33	70	4300	12946	5.65
19		119	5.6	34	72	4820	14475	6.25
20		120	6	35	75	5090	16310	7.00
22		127	6	38	82	6450	19368	8.55
25		140	6.6	40	88	8320	24975	10.90
28		152	7.0	42	96	12230	30581	13.90
32		171	7.8	44	108	16300	40775	18.20

# DIN 764

SIZE		INSIDE LENGTH		INSIDE WIDTH	OUTSIDE WIDTH	TEST LOAD	BREAKING LOAD	WEIGHT PER M
MM	±MM	MM	±MM	MM	MM	KG	KG	KG
6	0.20	21	0.50	8	21.5	680	1680	0.74
			0.20					
8	0.20	28	0.50	11	29	850	3620	1.315
			0.30					
10	0.30	35	0.60	14	36	1680	5090	2.00
			0.30					
13	0.40	45	0.70	18	47	2630	8150	3.50
			0.40					
16	0.50	56	0.90	22	58	4200	12740	5.20
			0.50					
18	0.80	63	1.00	24	65	6700	16300	6.50
			0.50					
20	1.00	70	1.10	27	72	8400	20380	8.20
			0.60					
23	1.20	80	1.30	31	83	10000	25480	11.00
			0.70					
26	1.30	91	1.50	35	94	13000	32610	14.00
			0.20					